

DL 185 GAR LED




Recessed LED luminaire. Body is made of steel and aluminium and it is available in all RAL colours. Light source - Philips, Osram or Tridonic LED module. Standard EVG ballast, DALI or Touch Dali version on request. Passive cooling, optional IP44 diffuser. Product is also available with special application LED modules: CrispWhite, Food WarmWhite, Food PremiumRed and many others - details on request.

High quality, energy efficient white LED light with CRI 80 and more.

Perfect replacement for conventional luminaires in:

- Offices
- Public buildings
- Hotel lobbies and receptions
- Retail



Index no.	Lumen output	Wattage	Colour temp.	Colour rendering index	Lifetime	Weight
004020.1100/827	1100 lm	9 W	2700 K	Ra > 80	50.000 h	1,75 kg
004020.1100/830	1100 lm	9 W	3000 K	Ra > 80	50.000 h	1,75 kg
004020.1100/840	1100 lm	8 W	4000 K	Ra > 80	50.000 h	1,75 kg
004020.2000/827	2000 lm	16 W	2700 K	Ra > 80	50.000 h	1,75 kg
004020.2000/830	2000 lm	15 W	3000 K	Ra > 80	50.000 h	1,75 kg
004020.2000/840	2000 lm	14 W	4000 K	Ra > 80	50.000 h	1,75 kg
004020.3000/827	3000 lm	24 W	2700 K	Ra > 80	50.000 h	1,75 kg
004020.3000/830	3000 lm	23 W	3000 K	Ra > 80	50.000 h	1,75 kg
004020.3000/840	3000 lm	21 W	4000 K	Ra > 80	50.000 h	1,75 kg

* Ra > 90 modules, different lumen output or wattage available on request.

* System power consumption (LED module & driver) depends on components used. Contact us for detailed information.

