

# DL 185 LOW VERSION



Recessed downlight for compact fluorescent lamps. Body (standard zinc, painted black on request) and ring (standard white, other colours on request) are made of steel. Reflector made of aluminium. Gearbox can be mounted on the top or remote on wire (for remote gearbox please add RGB after index number).

Technical extras upon request:

1. Emergency supply  
- battery pack 1/2/3h (please add EM1, EM2 or EM3 after index number)
2. Compensation or passive power (capacitor).  
Please add COMPENSATION after index number.
3. Dimmable ballast EVG DIM (1-10 V).  
Please add EVG DIM after index number.
4. Digital dimmable ballast (DALI).  
Please add DALI after index number.




Easy installation – without tools.



Mounting brackets.



Diamond faceted reflector (F).



Index no.	Lamp	Weight	Socket
F01.185.2037V	VVG, 1x13W TC-D	1,30 kg	G24d - 1
F01.185.2037E	EVG, 1x13W TC-DEL	1,10 kg	G24q - 1
F01.185.2038V	VVG, 1x18W TC-D	1,30 kg	G24d - 2
F01.185.2038E	EVG, 1x18W TC-DEL	1,10 kg	G24q - 2
F01.185.2039V	VVG, 2x13W TC-D	1,60 kg	G24d - 1
F01.185.2039E	EVG, 2x13W TC-DEL	1,30 kg	G24q - 1
F01.185.2040V	VVG, 2x18W TC-D	1,60 kg	G24d - 2
F01.185.2040E	EVG, 2x18W TC-DEL	1,30 kg	G24q - 2

With plain glossy reflector.

Index no.	Lamp	Weight	Socket
G01.185.2037V	VVG, 1x13W TC-D	1,30 kg	G24d - 1
G01.185.2037E	EVG, 1x13W TC-DEL	1,10 kg	G24q - 1
G01.185.2038V	VVG, 1x18W TC-D	1,30 kg	G24d - 2
G01.185.2038E	EVG, 1x18W TC-DEL	1,10 kg	G24q - 2
G01.185.2039V	VVG, 2x13W TC-D	1,60 kg	G24d - 1
G01.185.2039E	EVG, 2x13W TC-DEL	1,30 kg	G24q - 1
G01.185.2040V	VVG, 2x18W TC-D	1,60 kg	G24d - 2
G01.185.2040E	EVG, 2x18W TC-DEL	1,30 kg	G24q - 2

IP20

230 V  
50 Hz

