


# DL 220 DW




Recessed downlight for compact fluorescent lamps. Body (standard zinc, painted black on request) and ring (standard white, other colours on request) are made of steel. Reflector made of aluminium.

Technical extras upon request:

1. Emergency supply  
- battery pack 1/2/3h (please add EM1, EM2 or EM3 after index number)
2. Compensation or passive power (capacitor).  
Please add COMPENSATION after index number.
3. Dimmable ballast EVG DIM (1-10 V).  
Please add EVG DIM after index number.
4. Digital dimmable ballast (DALI).  
Please add DALI after index number.



Easy installation – without tools. DL220 DW Glass. DL220 DW Prisma.



Index no.	Lamp	Weight	Socket
<b>DL 220 DW Opal</b>			
101.220.6482V	VVG, 1x13W TC-D	1,65 kg	G24d - 1
101.220.6482E	EVG, 1x13W TC-DEL	0,90 kg	G24q - 1
101.220.6480V	VVG, 1x18W TC-D	1,65 kg	G24d - 2
101.220.6480E	EVG, 1x18W TC-DEL	1,50 kg	G24d - 2
101.220.6492V	VVG, 2x13W TC-D	2,00 kg	G24d - 1
101.220.6492E	EVG, 2x13W TC-DEL	1,65 kg	G24q - 1
101.220.6490V	VVG, 2x18W TC-D	2,00 kg	G24d - 2
101.220.6490E	EVG, 2x18W TC-DEL	1,65 kg	G24d - 2

Index no.	Lamp	Weight	Socket
<b>DL 220 DW with glass</b>			
100.220.6482V	VVG, 1x13W TC-D	1,65 kg	G24d - 1
100.220.6482E	EVG, 1x13W TC-DEL	0,90 kg	G24q - 1
100.220.6480V	VVG, 1x18W TC-D	1,65 kg	G24d - 2
100.220.6480E	EVG, 1x18W TC-DEL	1,50 kg	G24d - 2
100.220.6492V	VVG, 2x13W TC-D	2,00 kg	G24d - 1
100.220.6492E	EVG, 2x13W TC-DEL	1,65 kg	G24q - 1
100.220.6490V	VVG, 2x18W TC-D	2,00 kg	G24d - 2
100.220.6490E	EVG, 2x18W TC-DEL	1,65 kg	G24d - 2

Index no.	Lamp	Weight	Socket
<b>DL 220 DW Prisma</b>			
102.220.6482V	VVG, 1x13W TC-D	1,65 kg	G24d - 1
102.220.6482E	EVG, 1x13W TC-DEL	0,90 kg	G24q - 1
102.220.6480V	VVG, 1x18W TC-D	1,65 kg	G24d - 2
102.220.6480E	EVG, 1x18W TC-DEL	1,50 kg	G24d - 2
102.220.6492V	VVG, 2x13W TC-D	2,00 kg	G24d - 1
102.220.6492E	EVG, 2x13W TC-DEL	1,65 kg	G24q - 1
102.220.6490V	VVG, 2x18W TC-D	2,00 kg	G24d - 2
102.220.6490E	EVG, 2x18W TC-DEL	1,65 kg	G24d - 2