

DL 255 BASIC NEW




Recessed downlight for compact fluorescent lamps with flat IP44 glass. Body (standard zinc, painted black on request) is made of steel. Reflector made of aluminium.

Technical extras upon request:

1. Emergency supply
- battery pack 1/2/3h (please add EM1, EM2 or EM3 after index number)
2. Compensation or passive power (capacitor).
Please add COMPENSATION after index number.
3. Dimmable ballast EVG DIM (1-10 V).
Please add EVG DIM after index number.
4. Digital dimmable ballast (DALI).
Please add DALI after index number.



Easy installation – without tools. Mounting brackets. IP44 glass can be clear or matt.



Ø 235

Index no.	Lamp	Weight	Socket
274.255.2266V	VVG, 1x18W TC-D	2,05 kg	G24d - 2
274.255.2266E	EVG, 1x18W TC-DEL	1,90 kg	G24q - 2
274.255.2267V	VVG, 1x26W TC-D	2,15 kg	G24d - 3
274.255.2267E	EVG, 1x26W TC-DEL	1,90 kg	G24q - 3
274.255.2268V	VVG, 2x18W TC-D	2,25 kg	G24d - 2
274.255.2268E	EVG, 2x18W TC-DEL	1,95 kg	G24q - 2
274.255.2269V	VVG, 2x26W TC-D	2,45 kg	G24d - 3
274.255.2269E	EVG, 2x26W TC-DEL	1,95 kg	G24q - 3

IP44

230 V
50 HZ

