


DLK 140 LED



Recessed LED luminaire. Body is made of steel, reflector of aluminium. Available in all RAL colours. Light source - Philips, Osram or Tridonic LED module. Standard EVG ballast, DALI or Touch Dali version on request. Passive cooling, optional IP44 diffuser.



Index no.	Lumen output	Wattage	Colour temp.	Colour rendering index	Lifetime	Weight
With integrated AC driver						
004520.1100/830	1100 lm	12 W	3000 K	Ra > 80	50.000 h	2,10 kg
004520.1100/840	1100 lm	12 W	4000 K	Ra > 80	50.000 h	2,10 kg
004520.2000/830	2000 lm	28 W	3000 K	Ra > 80	50.000 h	2,10 kg
004520.2000/840	2000 lm	26 W	4000 K	Ra > 80	50.000 h	2,10 kg
With AC/DC driver						
005263.1100/830	1100 lm	12 W	3000 K	Ra > 80	50.000 h	2,30 kg
005263.1100/840	1100 lm	12 W	4000 K	Ra > 80	50.000 h	2,30 kg
005263.2000/830	2000 lm	20 W	3000 K	Ra > 80	50.000 h	2,30 kg
005263.2000/840	2000 lm	20 W	4000 K	Ra > 80	50.000 h	2,30 kg

* Different lumen output or wattage available on request.

* System power consumption (LED module & driver) depends on components used. Contact us for detailed information.

