

DLV 185



Recessed downlight for compact fluorescent lamps in vertical mode. Body (standard zinc, painted black on request) and ring (standard white, other colours on request) are made of steel. Reflector made of aluminium.


Technical extras upon request:

1. Emergency supply
- battery pack 1/2/3h (please add EM1, EM2 or EM3 after index number)
 2. Compensation or passive power (capacitor).
Please add COMPENSATION after index number.
 3. Dimmable ballast EVG DIM (1-10 V).
Please add EVG DIM after index number.
 4. Digital dimmable ballast (DALI).
Please add DALI after index number.
- All DLV 185 downlights are in standard with remote gearbox.



Easy installation – without tools.

Mounting brackets.



| Index no. | Lamp | Weight | Socket |
|-------------|-------------------|---------|----------|
| 09.185.113V | VVG, 1x13W TC-D | 0,95 kg | G24d - 1 |
| 09.185.113E | EVG, 1x13W TC-DEL | 0,80 kg | G24q - 1 |
| 09.185.118V | VVG, 1x18W TC-D | 1,00 kg | G24d - 2 |
| 09.185.118E | EVG, 1x18W TC-DEL | 0,85 kg | G24q - 2 |
| 09.185.126V | VVG, 1x26W TC-D | 1,00 kg | G24d - 3 |
| 09.185.126E | EVG, 1x26W TC-DEL | 0,85 kg | G24q - 3 |

IP20

230 V
50 Hz

