

DUO FORTIMO



Recessed adjustable LED luminaire.

Body is made of steel and aluminium and it is available in all RAL colours.



Light source - Philips, Osram or Tridonic LED module. Standard EVG ballast,

DALI or Touch Dali version on request. Passive cooling.

High quality, energy efficient white LED light with CRI 80 and more.

Applications:

- Retail: shop windows, wall - washing, accent and display lighting
- Hospitality: lobbies, reception areas, restaurants, bars, elevators
- Recreation: museums, galleries, theatres and other public places



387x190

Index no.	Lumen output	Wattage	Colour temp.	Colour rendering index	Lifetime	Weight
With integrated AC driver						
005268.21100/830	2 x 1100 lm	2 x 12 W	3000 K	Ra > 80	50,000 h	6,10 kg
005268.21100/840	2 x 1100 lm	2 x 12 W	4000 K	Ra > 80	50,000 h	6,10 kg
005268.22000/830	2 x 2000 lm	2 x 28 W	3000 K	Ra > 80	50,000 h	6,10 kg
005268.22000/840	2 x 2000 lm	2 x 26 W	4000 K	Ra > 80	50,000 h	6,10 kg
005268.23000/830	2 x 3000 lm	2 x 43 W	3000 K	Ra > 80	50,000 h	6,10 kg
005268.23000/840	2 x 3000 lm	2 x 39 W	4000 K	Ra > 80	50,000 h	6,10 kg
With AC/DC driver						
003059.21100/830	2 x 1100 lm	2 x 12 W	3000 K	Ra > 80	50,000 h	6,50 kg
003059.21100/840	2 x 1100 lm	2 x 12 W	4000 K	Ra > 80	50,000 h	6,50 kg
003059.22000/830	2 x 2000 lm	2 x 20 W	3000 K	Ra > 80	50,000 h	6,50 kg
003059.22000/840	2 x 2000 lm	2 x 20 W	4000 K	Ra > 80	50,000 h	6,50 kg
003059.23000/830	2 x 3000 lm	2 x 30 W	3000 K	Ra > 80	50,000 h	6,50 kg
003059.23000/840	2 x 3000 lm	2 x 30 W	4000 K	Ra > 80	50,000 h	6,50 kg

* Different lumen output or wattage available on request.

* System power consumption (LED module & driver) depends on components used. Contact us for detailed information.

