

# PROFI 60 R LED TB




Pendent, surface mounted or recessed LED luminaires.

- Opal in standard (OP) or acrylic diffuser (AC) on request
- Light source - Philips retrofit linear LED lamp included.
- Body made of aluminium profile and available in all RAL colours
- This luminaire can be mounted directly to the ceiling or pendent on steel wires and can be connected in long lighting lines.
- We can prepare it in different lengths and shapes on request.
- High quality, energy efficient white LED light with CRI 80.

Perfect replacement for conventional T5 luminaires in:

- Offices
- Public buildings
- Hotel lobbies and receptions
- Retail

Index no.	Lumen output	Wattage	Colour temp.	Colour rendering index	Lifetime	Length	Weight
005209.2300/830	2300 lm	20 W	3000 K	Ra > 80	50.000 h	1270 mm	1,50 kg
005209.2500/840	2500 lm	20 W	4000 K	Ra > 80	50.000 h	1270 mm	1,50 kg
005209.2500/865	2500 lm	20 W	6500K	Ra > 80	50.000 h	1270 mm	2,00 kg
005209.3400/830	3400 lm	25 W	3000 K	Ra > 80	50.000 h	1570 mm	2,00 kg
005209.3700/840	3700 lm	25 W	4000 K	Ra > 80	50.000 h	1570 mm	2,50 kg
005209.3700/865	3700 lm	25 W	6500K	Ra > 80	50.000 h	1570 mm	2,50 kg



L - 1250 x 64  
L - 1550 x 64

