

# QUATTRO SLM



Recessed adjustable LED luminaire.



Body is made of steel and aluminium and it is available in all RAL colours.

Light source - Philips, Osram or Tridonic LED module. Standard EVG ballast, DALI or Touch Dali version on request. Passive cooling. Product is also available with special application LED modules: CrispWhite, Food WarmWhite, Food PremiumRed and many others - details on request.

High quality, energy efficient white LED light with CRI 80 and more.

Applications:

- Retail: shop windows, wall - washing, accent and display lighting
- Hospitality: lobbies, reception areas, restaurants, bars, elevators
- Recreation: museums, galleries, theatres and other public places



Index no.	Lumen output	Wattage	Colour temp.	Colour rendering index	Lifetime	Weight
003072.41100/827	4 x 1100 lm	4 x 9 W	2700 K	Ra > 80	50.000 h	7,80 kg
003072.41100/830	4 x 1100 lm	4 x 9 W	3000 K	Ra > 80	50.000 h	7,80 kg
003072.41100/840	4 x 1100 lm	4 x 8 W	4000 K	Ra > 80	50.000 h	7,80 kg
003072.42000/827	4 x 2000 lm	4 x 16 W	2700 K	Ra > 80	50.000 h	7,80 kg
003072.42000/830	4 x 2000 lm	4 x 15 W	3000 K	Ra > 80	50.000 h	7,80 kg
003072.42000/840	4 x 2000 lm	4 x 14 W	4000 K	Ra > 80	50.000 h	7,80 kg
003072.43000/827	4 x 3000 lm	4 x 24 W	2700 K	Ra > 80	50.000 h	7,80 kg
003072.43000/830	4 x 3000 lm	4 x 23 W	3000 K	Ra > 80	50.000 h	7,80 kg
003072.43000/840	4 x 3000 lm	4 x 21 W	4000 K	Ra > 80	50.000 h	7,80 kg
003072.41100/927	4 x 1100 lm	4 x 11 W	2700 K	Ra > 90	50.000 h	7,80 kg
003072.41100/930	4 x 1100 lm	4 x 11 W	3000 K	Ra > 90	50.000 h	7,80 kg
003072.41100/940	4 x 1100 lm	4 x 10 W	4000 K	Ra > 90	50.000 h	7,80 kg
003072.42000/927	4 x 2000 lm	4 x 19 W	2700 K	Ra > 90	50.000 h	7,80 kg
003072.42000/930	4 x 2000 lm	4 x 19 W	3000 K	Ra > 90	50.000 h	7,80 kg
003072.42000/940	4 x 2000 lm	4 x 17 W	4000 K	Ra > 90	50.000 h	7,80 kg
003072.43000/927	4 x 3000 lm	4 x 28 W	2700 K	Ra > 90	50.000 h	7,80 kg
003072.43000/930	4 x 3000 lm	4 x 28 W	3000 K	Ra > 90	50.000 h	7,80 kg
003072.43000/940	4 x 3000 lm	4 x 25 W	4000 K	Ra > 90	50.000 h	7,80 kg
003072.43000/930CW	4 x 3000 lm	4 x 34 W	3000 K	Ra > 90	50.000 h	7,80 kg
003072.43800/930CW	4 x 3800 lm	4 x 42 W	3000 K	Ra > 90	50.000 h	7,80 kg
003072.42800/925FW	4 x 3000 lm	4 x 42 W	2900 K	Ra > 90	50.000 h	7,80 kg
003072.43000/930FR	4 x 3000 lm	4 x 42 W	3150 K	Ra > 80	50.000 h	7,80 kg

\* Different lumen output or wattage available on request.

\* System power consumption (LED module & driver) depends on components used. Contact us for detailed information.

